



Mostly used by the printing industry for the lamination of offset and digital printouts, such as catalogues, books, booklets, leaflets etc. The lamination permits to obtain a gloss or matt finishing, to bring out the details or enforce the colours. Films also secure from mechanical, chemical and humidity factors.

Laminating machine Excelam Hot II 355 Q

Laminating machine Excelam Hot II 355 Q

- roll laminating machine with hot rollers coated with silicone
- thickness of laminating pouches between 32 - 250 mic
- for hot and cold lamination
- adjustable working gap - up to 5 mm - allows to stick on foam cardboard
- switch to reverse the work's direction
- laser temperature measurement sensor
- microprocessor temperature and speed control
- modern liquid-crystal (LCD) steering panel
- easy-to-use control system of the roller's pressure and of the film stress
- maximum laminating speed: 1.6 m/min
- maximum lamination width: 350 mm
- warranty: 2 years

Max paper format	A3+ (303 x 426 mm)
Max lamination width	350 mm
Number of heating rollers	4
Max thickness of laminating pouches	250 mic
Lamination speed	1600 mm/min
Heating time	7 minut
Cold lamination	yes
No need to use carriers	yes
Permits to laminate a photo	yes
Perform decorations with the metallized stamping foil	no
Fully automatic work	no
Dimansions	546x456x285 mm